# Datasheet and description



# Avide LED Flood Light Slim 20W NW 4000K

**Product code:** ABSFLNW-20W

**Brand link:** avidelighting.com/qr/ABSFLNW-20W

**ID:** AB-190518

**Company name:** Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



**Date of issue:** 2023-01-20

Page: 1/3

## **SPECIFICATIONS**

EAN code: 5999562284360

Warranty: 3year(s)
Working temperature:  $-20 - +40 \, ^{\circ}\text{C}$ Packaging:  $1/b \, 15/c \, 720/p$ 

Certifications: CE

#### **TECHNICAL DETAILS**

Wattage: 20W
Voltage: 85-265V
Beam angle: 120°
Dimmability: No

Lumen output: 1 800lm
Color temperature: 4 000K
Lifetime: 25 000h

Energy class: G

Type of LED: COB

Driver: CCD

CRI: >80

IP standard: IP65

## **BOX PICTURE**



# Datasheet and description



# Avide LED Flood Light Slim 20W NW 4000K

**Product code:** ABSFLNW-20W

**Brand link:** avidelighting.com/qr/ABSFLNW-20W

**ID:** AB-190518

**Company name:** Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 2/3

#### **PRODUCT SIZE**

Width: 155mm
Height: 186mm
Depth: 50mm

#### **CARDBOARD BOX**

EAN: 5999562284360 Packaging: 1/b 15/c 720/p

Dimensions: 145mm x 50mm x 200mm

Net weight: 725g Gross weight: 797g

## **CARTON**

EAN: 5999562284407 Packaging: 1/b 15/c 720/p

Dimensions: 445mm x 275mm x 220mm

Net weight: 10.875kg Gross weight: 11.955kg

### **PALLET EXAMPLE**

Height:

Width: 120cm (std Euro pallet)

Mepth: 80cm (std Euro pallet)


Cartons per pallet: 48carton/pallet

Cartons per row: 6pcs
Net weight: 522kg
Gross weight: 573.84kg

#### **PRODUCT PICTURE**



## **PRODUCT OUTLINE**



## Datasheet and description



# Avide LED Flood Light Slim 20W NW 4000K

Product code: ABSFLNW-20W

**Brand link:** avidelighting.com/qr/ABSFLNW-20W

**ID:** AB-190518

**Company name:** Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 3/3

#### **PRODUCT DESCRIPTION**

The battery-operated Avide COB LED floodlights enable portable, mobile use. Brightness is adjustable in two stages. They can provide the same brightness as traditional halogen floodlights but with much lower power consumption; thus when operated from a battery, they can ensure a longer operating time. The battery of the floodlight can be fully charged in 3 hours and with one full charge it can operate for up to 5 hours. COB (chip-on-board) represents one of the most recent LED technologies, focusing the emitted light much better and thus providing better lighting at a longer distance. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide COB Floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W / 80W / 100W / 150W power output versions. The "SLIM" design is also available in neutral white (NW) / cold white (CW) color temperatures and a 10W / 20W / 30W / 50W power output.