

## Avide LED Flood Light Slim SMD 10W CW 6400K

<b>Product code:</b>	ABSSFLCW-10W
<b>Brand link:</b>	<a href="http://avidelighting.com/qr/ABSSFLCW-10W">avidelighting.com/qr/ABSSFLCW-10W</a>
<b>ID:</b>	AB-190518
<b>Company name:</b>	Armin Trade Kft.
<b>Company address:</b>	Kossuth utca 22 2/4, 4024 Debrecen

QR code:



Date of issue: 2023-01-20

Page: 1/3

### SPECIFICATIONS

EAN code:	5999097914084
Warranty:	3year(s)
Working temperature:	-20 - +40 °C
Packaging:	1/b 60/c 1200/p
Certifications:	CE

### TECHNICAL DETAILS

Wattage:	10W
Voltage:	220-240V
Beam angle:	120°
Dimmability:	No
Lumen output:	820lm
Color temperature:	6 400K
Lifetime:	25 000h
Energy class:	F
Type of LED:	SMD
Driver:	Linear IC
CRI:	>80
IP standard:	IP65

### BOX PICTURE



## Avide LED Flood Light Slim SMD 10W CW 6400K

<b>Product code:</b>	ABSSFLCW-10W
<b>Brand link:</b>	<a href="https://avidelighting.com/qr/ABSSFLCW-10W">avidelighting.com/qr/ABSSFLCW-10W</a>
<b>ID:</b>	AB-190518
<b>Company name:</b>	Armin Trade Kft.
<b>Company address:</b>	Kossuth utca 22 2/4, 4024 Debrecen

QR code:



Date of issue: 2023-01-20

Page: 2/3

### PRODUCT SIZE

Width:	92mm
Height:	67mm
Depth:	32mm

### CARDBOARD BOX

EAN:	5999097914084
Packaging:	1/b 60/c 1200/p
Dimensions:	85mm x 115mm x 50mm
Net weight:	250g
Gross weight:	315g

### CARTON

EAN:	5999097914091
Packaging:	1/b 60/c 1200/p
Dimensions:	475mm x 350mm x 290mm
Net weight:	15kg
Gross weight:	18.9kg


### PALLET EXAMPLE

Height:	
Width:	120cm (std Euro pallet)
Mepth:	80cm (std Euro pallet)
Cartons per pallet:	20carton/pallet
Cartons per row:	
Net weight:	300kg
Gross weight:	378kg

### PRODUCT PICTURE



### PRODUCT OUTLINE



## Avide LED Flood Light Slim SMD 10W CW 6400K

<b>Product code:</b>	ABSSFLCW-10W
<b>Brand link:</b>	<a href="https://avidelighting.com/qr/ABSSFLCW-10W">avidelighting.com/qr/ABSSFLCW-10W</a>
<b>ID:</b>	AB-190518
<b>Company name:</b>	Armin Trade Kft.
<b>Company address:</b>	Kossuth utca 22 2/4, 4024 Debrecen

QR code:



Date of issue: 2023-01-20

Page: 3/3

### PRODUCT DESCRIPTION

The Avide SMD LED floodlights can provide the same brightness as traditional halogen lights but with a much lower power consumption, thus significant savings can be realized with their use. LED floodlights provide up to 20 times longer lifetime compared to products using traditional light bulbs. With their IP65 classification, they are also perfectly suitable for outdoor use. The edge of the floodlight features a movable metal frame, thus you can fix it on the ground, the wall or even the ceiling. After mounting, the angle can be adjusted anytime, thus it will provide the light you need exactly where you need it.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide SMD floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W power output versions, as well as in a neutral white (NW) color temperature and a 100W / 150W / 200W power output.