Datasheet and description



Avide LED Flood Light Slim SMD 30W CW 6400K

Product code: ABSSFLCW-30W

Brand link: avidelighting.com/qr/ABSSFLCW-30W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 1/3

SPECIFICATIONS

EAN code: 5999097914121

Warranty: 3year(s)
Working temperature: -20 - +40 °C
Packaging: $1/b \ 40/c \ 630/p$

Certifications: CE

TECHNICAL DETAILS

Wattage: 30W
Voltage: 220-240V
Beam angle: 120°

Dimmability: No

Lumen output: 2 270lm
Color temperature: 6 400K
Lifetime: 25 000h

Energy class: F
Type of LED: SMD
Driver: Linear IC
CRI: >80

IP65

IP standard:

BOX PICTURE



Datasheet and description



Avide LED Flood Light Slim SMD 30W CW 6400K

Product code: ABSSFLCW-30W

Brand link: avidelighting.com/qr/ABSSFLCW-30W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 2/3

PRODUCT SIZE

Width: 137mm
Height: 97mm
Depth: 33mm

CARDBOARD BOX

EAN: 5999097914121 Packaging: 1/b 40/c 630/p

Dimensions: 120mm x 165mm x 65mm

Net weight: 350g Gross weight: 380g

CARTON

EAN: 5999097914138 Packaging: 1/b 40/c 630/p


Dimensions: 625mm x 345mm x 260mm

Net weight: 14kg Gross weight: 15.2kg

PRODUCT PICTURE



PRODUCT OUTLINE



PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)

Cartons per pallet: 15carton/pallet

Cartons per row:

Net weight: 220.5kg Gross weight: 239.4kg

Datasheet and description



Avide LED Flood Light Slim SMD 30W CW 6400K

Product code: ABSSFLCW-30W

Brand link: avidelighting.com/qr/ABSSFLCW-30W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 3/3

PRODUCT DESCRIPTION

The Avide SMD LED floodlights can provide the same brightness as traditional halogen lights but with a much lower power consumption, thus significant savings can be realized with their use. LED floodlights provide up to 20 times longer lifetime compared to products using traditional light bulbs. With their IP65 classification, they are also perfectly suitable for outdoor use. The edge of the floodlight features a movable metal frame, thus you can fix it on the ground, the wall or even the ceiling. After mounting, the angle can be adjusted anytime, thus it will provide the light you need exactly where you need it.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide SMD floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W power output versions, as well as in a neutral white (NW) color temperature and a 100W / 150W / 200W power output.