Datasheet and description

Avide LED Flood Light Slim SMD 50W CW 6400K

Product code: ABSSFLCW-50W

Brand link: avidelighting.com/qr/ABSSFLCW-50W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen

QR code:

Date of issue: 2023-01-20

SPECIFICATIONS

EAN code:	5999097914145
Warranty:	3year(s)
Working temperature:	-20 - +40 °C
Packaging:	1/b 20/c 480/p
Certifications:	CE

TECHNICAL DETAILS

Wattage:	50W
Voltage:	220-240V
Beam angle:	120°
Dimmability:	No
Lumen output:	5 000lm
Color temperature:	6 400K
Lifetime:	25 000h
Energy class:	F
Type of LED:	SMD
Driver:	Linear IC
CRI:	>80
IP standard:	IP65

BOX PICTURE

Datasheet and description

Avide LED Flood Light Slim SMD 50W CW 6400K

Product code: ABSSFLCW-50W

Brand link: avidelighting.com/qr/ABSSFLCW-50W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen

QR code:

Date of issue: 2023-01-20

PRODUCT SIZE

Width:	211mm
Height:	140mm
Depth:	33mm

CARDBOARD BOX

EAN:	5999097914145
Packaging:	1/b 20/c 480/p
Dimensions:	160mm x 215mm x 65mm
Net weight:	640g
Gross weight:	654g

CARTON

EAN:	5999097914152
Packaging:	1/b 20/c 480/p
Dimensions:	445mm x 320mm x 340mm
Net weight:	12.8kg
Gross weight:	13.08kg

PALLET EXAMPLE

Height:	
Width:	120cm (std Euro pallet)
Mepth:	80cm (std Euro pallet)
Cartons per pallet:	24carton/pallet
Cartons per row:	
Net weight:	307.2kg
Gross weight:	313.92kg

PRODUCT PICTURE

PRODUCT OUTLINE



Datasheet and description

Avide LED Flood Light Slim SMD 50W CW 6400K

Product code:	ABSSFLCW-50W
Brand link:	avidelighting.com/qr/ABSSFLCW-50W
ID:	AB-190518
Company name:	Armin Trade Kft.
Company address:	Kossuth utca 22 2/4, 4024 Debrecen

QR code:

Date of issue: 2023-01-20

PRODUCT DESCRIPTION

The Avide SMD LED floodlights can provide the same brightness as traditional halogen lights but with a much lower power consumption, thus significant savings can be realized with their use. LED floodlights provide up to 20 times longer lifetime compared to products using traditional light bulbs. With their IP65 classification, they are also perfectly suitable for outdoor use. The edge of the floodlight features a movable metal frame, thus you can fix it on the ground, the wall or even the ceiling. After mounting, the angle can be adjusted anytime, thus it will provide the light you need exactly where you need it.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide SMD floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W power output versions, as well as in a neutral white (NW) color temperature and a 100W / 150W / 200W power output.