

Avide LED T5 Integrated Tube Connector Cable

Product code: ABT5-CON
Brand link: avidelighting.com/qr/ABT5-CON
ID: AB-190518
Company name: Armin Trade Kft.
Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 1/3

SPECIFICATIONS

EAN code: 5999097909967
Warranty: 2year(s)
Working temperature:
Packaging: 1/b
Certifications: CE

PRODUCT PICTURE



TECHNICAL DETAILS

Wattage:
Voltage: 220-240V
Beam angle:
Dimmability: No
Lumen output:
Color temperature:
Lifetime:
Energy class:
Type of LED: SMD
IP standard: IP20

Avide LED T5 Integrated Tube Connector Cable

Product code: ABT5-CON
Brand link: avidelighting.com/qr/ABT5-CON
ID: AB-190518
Company name: Armin Trade Kft.
Company address: Kossuth utca 22 2/4, 4024 Debrecen

QR code:



Date of issue: 2023-01-20

Page: 2/3

PRODUCT SIZE

Diameter:
Length: 150mm

PRODUCT PICTURE



CARDBOARD BOX

EAN: 5999097909967
Packaging: 1/b
Dimensions: 180mm x 10mm x 30mm
Net weight: 44g
Gross weight: 51.2g

PRODUCT OUTLINE

CARTON

EAN: 5999097909974
Packaging: 1/b
Dimensions:
Net weight: 0.044kg
Gross weight: 0.0512kg

PALLET EXAMPLE

Height:
Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)
Cartons per pallet: 1carton/pallet
Cartons per row:
Net weight: 0.044kg
Gross weight: 0.0512kg

Avide LED T5 Integrated Tube Connector Cable

Product code:	ABT5-CON
Brand link:	avidelighting.com/qr/ABT5-CON
ID:	AB-190518
Company name:	Armin Trade Kft.
Company address:	Kossuth utca 22 2/4, 4024 Debrecen

QR code:



Date of issue: 2023-01-20

Page: 3/3

PRODUCT DESCRIPTION

The Avide LED integrated dust- and moisture-proof fixtures represent the modern versions of traditional fittings. The fixtures of different lengths replacing the tube fixtures have a built-in LED panel that guarantees energy-saving operation. In terms of the material used, the products have a break-resistant cover. Due to the IP65 protection of the fixture, it is protected from dust and moisture, thus can also be operated at places with higher exposure to dust and humidity.

The product range includes 3 different lengths and brightness levels, available in neutral white color temperature and with an opaline cover. The 60cm fixture has 20W power, while the 120 centimeter version has a 40W and the 150 centimeter type a 60W power output respectively.