Datasheet and description



Avide LED Flood Light Slim SMD 10W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-10W

Brand link: avidelighting.com/qr/ABSSTFLNW-10W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 1/3

SPECIFICATIONS

EAN code: 5999097919300

Warranty: 3year(s)
Working temperature: -20 - +50°C
Packaging: $1/b \ 10/c \ 480/p$

Certifications: CE

TECHNICAL DETAILS

Wattage: 10W

Voltage: AC180-240V

Beam angle: 120° Dimmability: No

Lumen output: 1 000lm
Color temperature: 4 000K
Lifetime: 30 000h

Energy class: F
Type of LED: SMD

Driver:

CRI: >70
IP standard: IP65

BOX PICTURE



Datasheet and description



Avide LED Flood Light Slim SMD 10W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-10W

Brand link: avidelighting.com/qr/ABSSTFLNW-10W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 2/3

PRODUCT SIZE

Width: 130mm
Height: 192mm
Depth: 100mm

CARDBOARD BOX

EAN: 5999097919300 Packaging: 1/b 10/c 480/p

Dimensions: 193mm x 210mm x 75mm

Net weight: 585g Gross weight: 600g

CARTON

EAN: 5999097919317
Packaging: 1/b 10/c 480/p

Dimensions: 395mm x 395mm x 230mm

Net weight: 5.85kg Gross weight: 6kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)

Cartons per pallet: 48carton/pallet

Cartons per row:

Net weight: 280.8kg
Gross weight: 288kg

PRODUCT PICTURE



PRODUCT OUTLINE

Datasheet and description



Avide LED Flood Light Slim SMD 10W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-10W

Brand link: avidelighting.com/qr/ABSSTFLNW-10W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-01-20

Page: 3/3

PRODUCT DESCRIPTION

Light your work area with the Avide SMD portable LED floodlights. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

Do not look directly into the floodlight! Do not use the fixture under water!

Due to its portability, you can take it where an extra light source is needed the most. The 3G0.75 type and 1.5-meter-long power cable provides convenient access to the power source.

The Avide SMD Floodlights are available in a neutral white (NW) color temperature and 10W, 20W, 30W and 50W power output versions.